### MINERAL SURVEY No. 4009

	ARIZONA	Land Dis	strict.
OF T	FIELD NO		
	Thomas B. Scot	<b>t</b> ,	***************************************
	KNOWN AS T	HE	
PAY ROLL	and BLACK PRINCE	lodes,	
			Mining District,
Mohave	County,	Arizona.	
Section2	, Township 23 Nor	th , Range	18 West
Surveyed under inst	ructions datedA	pril 21st., 1	9 26.
	by <u>Н</u>	arry E. Jones U.	S. Mineral Surveyor.
Claim located	See location	notices,	, 19
Survey comm	enced July 9th.		, 19 26 ,
Survey comple	eted July 10th	•	, 19 26 .
	Att'y. fo	or claimant.	Arizona.

Feet

#### MINERAL SURVEY NO. 4009

#### Pay Roll Lode

Beginning at Cor. No. 1, a 31ft. Zin. pipe with a 2 in. brass cap marked U.S.MINERAL SURVEY NO.4009-1-PR:2-RP: set 18ins. in ground and surrounded with a substantial mound of earth and rock, identical with the loc. mon. and Cor. 2 LASS BY TO DE TO BE Black Prince lode of this survey.

ite of .51 10.03

Cor. 3 Rattler lode Sur. No. 850 bears N. 76°55'E. 22.36 ft. A large granite boulder marked BxR-RM-3 bears N.66°27'W. cool out dity feetanai . soon 83.93 ft.

The No corner of Section 2, T. 23 N. R. 18 W. bears N. 7° 56'W. 1163.58 ft. No other suitable bearings available. expessed university to the expess

Thence S. 37° 43' 40" E.

- 9.19 Intersect line 3-4 Rattler lode Sur. No. 850 at S. 52°46'W. 20.28 ft. from Cor.3.
- 80.00 Cross center of 5 ft. wash, course Southwesterly,
- 1180.00 Cross center of 3 ft. wash, course Southwesterly.
- 1427.09 To Cor. No. 2, a 32ft. 4in. pipe with a 2 in. brass cap marked U.S.MINERAL SURVEY NO. 4009-2-PR; set 16 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the loc. mon.

A granite boulder 4x5x6 ft. exposed marked BxR-2-PR bears S.88°43'E. 43.30 ft.

A granite boulder 2x3x4 ft. exposed marked BxR-2-PR bears N.16°40'E. 51.30 ft.

Cor. 2 Rattler lode, Sur, No. 850, bears S. 43°09'E. 7.7.67ft. No other suitable bearings available.

Thence S. 43° 25' W.

- 298.60 To Southeast End Center, a substantial mound of stone, identical with the loc. mon.
- 475.50 Intersect line 5-2 Rattler lode, Sur.No. 850 at N.52°46'E. 120.81 ft. from Cor. 5.
- 598.60 To Cor. No. 3, a 31ft. in. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4009-3-PR; set 18 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the loc. mon.

Cor. 5 Rattler lode, Sur. No. 850 bears N.35°21'30"W. Feet 20.01 ft. No other suitable bearings available.

#### Thence N. 37° 47' W.

375.00 Cross center of 5 ft. wash, course Westerly,

1205.00 Cross center of 5 ft. wash, course Southwesterly.

1250.00 Cross center of road, bears NEly. and SWly.

1426.87 To Cor. No. 4, a 32ft. Lin. pipe with a 2in. brass cap marked U.S.MINERAL SURVEY NO.4009-4-PR; 3-BP; set 18 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the loc. mon. and Cor. 3 Black Prince lode of this survey.

Cor. 4 Rattler lode, Sur. No. 850 bears N. 28°W. 89.44 ft. A granite boulder 2x3x3 ft. exposed marked BxR-4-RM bears N.11°09'W. 154.71 ft. No other suitable bearings available.

#### Thence N. 43° 25' E.

Along line 3-2 Black Prince lode of this survey.

- 14.54 Intersect line 4-5 Rattler lode, Sur.No. 850, at \$.37°14' E. 85.92 ft. from Cor. 4. 1427.00 So Car. To. E. a 31ts.
- 300.00 To Northwest End Center, a substantial mound of stone, identical with the loc. mon. and the Southeast End Center Black Prince lode of this survey.
- 543.41 Intersect line 3-4 Rattler lode, Sur. No. 850, at S.52° 46 W. 76.20 ft. from Cor. 3,
- 600.00 To Cor. No. 1 the place of beginning.

77.67

#### Black Prince Lode

TICTUE S. GBCCOTT. Beginning at Cor. No. 1, a 31ft. in pipe with a 2in.brass cap marked U.S.MINERAL SURVEY NO. 4009-1-BP; set 20 ins. in ground and surrounded with a substantial mound of earth and rock, identical with the loc. mon.

Cor S Hatel

A granite rock in place 15x18x20 in. exposed, marked BxR-1-BP+ bears N.54°54'W. 26.73 ft.

A granite rock in place 3x4x5 ft. exposed, marked BxR-1-BP; bears N.6°29'W. 39.00 ft.

The Nt Cor. of Section 2, T. 23 N. R. 18 W. bears N. 73° 49' E. 1121.39 ft. No other suitable bearings available.

Thence S. 55° 50' E.

Feet

Roll lode of this survey, previously described.

Thence S. 43° 25' W.

Along line 1-4 Pay Roll lode of this survey.

- 56.59 Intersect line 3-4 Rattler lode, Sur. NO. 850, at N.52°
  46'E. 521.84 ft. from Cor. 4,
- 300.00 To Southeast End Center, a substantial mound of stone, identical with the loc. mon. and the Northwest End Center Pay Roll lode of this survey.
- 585.46 Intersect line 4-5 Rattler Lode Sur.No.850, at S.37°14'E.
  85.92 ft. from Cor. 4.
- Pay Roll lode of this survey, previously described.

Thence N. 55° 50' W.

- 1441.19 Intersect line 2-3 Burlock lode, Sur. No. 3520 at N.30° 51'30"W. 346.62 ft. from Cor. 3,
- 1495.68 to Cor. No. 4, a 32ft. in. pipe with a/brass cap marked
  U.S.MINERAL SURVEY, NO.4009-4-BP; set 18 ins. in ground and
  surrounded with a substantial mound of earth and rock,
  identical with the loc. mon.

Point for Print for Print

Thence N. 43° 25' E.

- 23.90 Intersect line 2-3 Burlock lode, Sur. No. 3520, at N. 30.51'30' w. 402.49 ft from Gor. No. 3. 300.00 To Northwest End Center, a substantial mound of stone, identical with the loc. mon.
- 600.00 to Cor. No. 1 the place of beginning.

high in covered on the curines

The mean magnetic variation at all corners is 15°20'East.

# LODE LINES

As near as can be determined from the present development the veins of the locations embraced in this claim extend as follows from their respective discovery points:

Pay Roll lode, N.37°47'W. 660 ft. and S.37°47'E. 766.87 ft.

Black Prince lode, N.55°50'W. 1495 ft. and S.55°50'E. 0.68 ft.

ively; ... 29 28 28 .. with a cross out to Mig. isspec

#### AREA

Total area Pay Roll lode,

19.400 Acres.

Area in conflict with:

Rattler lode, Sur. No. 850,

19.120

Mass for To Lot, No. S. identi

Total area Black Prince lode,

20-334

Area in conflict with:

Rattler lode, Sur. No. 850,

0.515

Burlock lode, Sur. No. 3520,

0.015

#### LOCATION

This survey is located in Section 2, T. 23 N. R. 18 W. Gila and Salt River Base and Meridian, Mohave County, Arizona.

#### EXPENDITURE OF. FIVE HUNDRED DOLLARS

made upon or for the benefit of the locations embraced in said mining claim by the claimant or his grantors is not less than Five Hundred Dollars, and that said improvements consist of:

#### Pay Roll Lode

No.1 Dis. cut 2x10x3 ft. bears S.37°47'E. 660 ft. from

NW. end center. Value \$ 25.00

No.2 shaft 7x10x610 ft. deep timbered, the center of which bears S.89°32'E. 328 ft. from Cor. 4.

The 50 ft. level in this shaft runs as follows:

N.59°41'E. 426x12 ft. thence N.46°32'E. 60.6 ft. thence(1)

then N.38°44'W. 19 ft. thence N.87°55'E. 15 ft. to face,

and S.87°55'W. 43 ft. thence N.25°40'E. in crosscut 4x6x21

ft. and S.82°30'W. 39.3 ft. thence S.57°40'W. 80 ft. thence

S.45°41'W.37.5 ft. to portal which is covered on the surface

by the dump.

(10) thence S.34°35'E. 34.2 ft. thence S.31°46'E. 72.4 ft. S.42°37'E. 108 ft. with crosscuts to NEly. at the 9 ft. and 58 ft. points of 15 ft. and 22 ft. long respectively; thence S.52°35'E. 102.3 ft. with crosscuts to NEly at the 13 ft. and 62 ft. points of 18 ft. and 20 ft. long respectively; S.29°25'E. 68.8 ft. with a cross cut to NEly. from

the 10 ft. point of 4x6x25 ft. long. Thence S.19°35'E.

99 ft. to face; with a crosscut from the 41 ft. point
bearing S.49°15'E. 15ft. thence N.87°E. 28 ft. to face.

The 200 ft. level in this shaft runs as follows:

(1)

N.56°23'E. 36.7 ft./thence N.3°W. 22.1 ft. thence N.15°20'

E. 38.8 ft. thence N.69°02'W. 23.6 ft. thence N.76°13'W.

32 ft. to face, and N.36°59'W. 28.7 ft. thence N.65°53'W.

50.5 ft. to face. (1) thence N.22°23'E. 15 ft. thence

N.59°25'E. 27.7 ft. thence N.89°44'E. 34 ft. to face, and

S.35°35'E. 34.2 ft. thence S.41°54'E. 120 ft. with crosscuts to to NEly. from the 48 ft. and 100 ft. points of

20 and 25 ft. respectively, thence S.59°10'E. 41 ft. to
face.

The 400 ft. level in this shaft runs as follows:

N.50°E. 50 ft. thence N.55°E. 26 ft. (1) thence N.36°W. 98 ft. thence N.71°W. 34 ft. thence N.46°W. 22 ft. thence

N.40°W. 53 ft. thence N.82°W. 32 ft. to face. (1) thence

S.35°E. 33 ft. thence S.45°E. 29 ft. thence S.56°E. 31 ft. thence S. 55°E. 73 ft. thence S.58°E. 56 ft. to face.

The 600 ft. level runs as follows from this shaft:

N.55°E. 135 ft. all of the foregoing drifts and crosscuts are 4x6 ft.

Total Value \$ 47, 896.00

This shaft and its lateral workings when considered from

a practical mining viewpoint should be accredited as the main working shaft of this claim, as it is centrally located and the bottom of the present shaft is several hundred feet below the level of the general surface of these lodes, and any work done in this shaft or along the vein which runs continuously the length of this claim will tend to develop the ore resources of both lodes and will be the most economical method of extracting the ore there from, therefore redounding to the benefit of both lodes, I therefore accredit an undivided ½ interest in this improvement to each of these lodes.

Value 2 \$ -23,948.00

No.3 tunnel 4x6x74 ft. long bearing N.35°W. bears S.4°
22'W. 189 ft. from NW. end center Value \$ 888.00

No.4 tunnel 4x6x40 ft. long bears NWly. bears S.55°28'E. 70 ft. from from the NW. end center. Value No.5 tunnel 4x6x25 ft. long bears NWly. bears S.79°53'E. 82 ft. from the NW. end center. Value \$ 300.00 No.6 tunnel 4x6x50 ft. long bearing NWly. bears N.46°52'E. 78 ft. from the NW. end center, Value As this improvement is approximately half on this lode and half on the Black Prince lode of this survey, I therefore accredit, an undivided interest in said improvement to this lode, Value 2 \$ 300.00 No.7 shaft 5x8x5 ft. deep bears S.65°05'E. 695 ft. from Cor. 4. No.8 cut 4x12x7 ft. facing SWly. bears N.57°42'E. 293 ft. from the 580.76 ft. point on line 3-4, Value No. 9) cut 4x10x8 ft. and tunnel 4x6x20 ft. long facing SWly. bears N.61°02'E. 293 ft. from the 580.76 ft. point on line 3-4, \$ 300.00 Value No.10 cut 4x15x8 ft. and tunnel 4x6x12 ft. long facing Sly. bears N.74°02'E. 321.ft. from the 580.76 ft. point on line 3-4. Value \$ 200.00 No.11 tunnel 4x6x100 ft. long partly caved, bearing NEly. bears S.89°52'E. 348 ft. from the 580.76 ft. point on line Value 344. \$ 1200.00 No.12 tunnel 4x6x 100 ft. long partly caved, bearing SEly. bears S.88°08'E. 414 ft. from the 580.76 ft. point on \$ 1200.00 line 3-4. Value No.13 cut 4x15x4ft. facing NWly. bears S.77°48'E. 474 ft. Value 75.00 from the 580.76 ft. on line 3-4, Value of 15 ft. of improvement No. 1 on the Black Prince lode of this survey is accredited to this lode, se sawyey to the extent

#### BLACK PRINCE lode.

No. 1, cut 5 x 30 x 15 ft. face, and tunnel 4 x 6 x 75

ft. long, discovery point in cut brs. N. 55° 50' W. .68

ft. from the S.E.End Center, extends thence S. 70° 23'

E. 15 ft. to mouth of cut, and N. 55° 50' W. 90 ft. to

face of tunnel.

Value, \$1200.00

15 ft. of this improvement is on the Pay Roll lode of this survey and is accredited to said lode.

Value of portion on this claim, \$1100.00

No.2 cut 4x12x6 ft. facing SEly. bears N.35°32'E. 54 ft.

from the SE. end center, Value \$ 100.00

An undivided ½ interest in improvement No.2 Pay Roll lode
of this survey is accredited to this lode,

Value \$ 23,948.00
An undivided \$ interest in improvement No. 6 Pay Roll lode
of this survey is accredited to this lode,
Value \$300.00

The SW cor. corrugated iron house lox12 ft. bears S.62° 41'E. 301 ft. from Cor. No. 4 Pay Roll lode.

The SW. cor. corrugated iron shop 18x20 ft. bears S.79° .38'E. 304 ft. from .Cor.4 Ray Roll lode.

The SW. cor. corrugated iron hoist and machine shop 20x40 ft. bears N.88°29'E. 334 ft. from Cor.4 Ray Roll lode,
The SW. cor corrugated iron house 12x16 ft. bears N.80°
52'E. 300 ft. from Cor. 4 Fay Roll lode.

The SE. cor. frame ore bin 18x32 ft. bears N.72°07'E. 232 ft. from Cor. 4 Pay Roll lode.

A cut and tunnel running N.70°E. bears N.76°52'E. 350 ft. from Cor. 4 Pay Roll lode.

A shaft 4x6x45 ft. deep bears S.86°53'E. 443 ft. from Cor. 4 Pay Roll lode.

A shaft 4x6x50 ft. deep bears S.65°33'E. 685 ft. from Cor. 4 Pay Roll lode.

A cut 4x45x17 ft. facing SEly. bears N.47°52'E. 294 ft. from the 580.76 ft. point on line 3-4 Pay Roll lode.

#### ADJOINING CLAIMS

This claim is bounded on the the West by the Burlock lode Sur. No. 3520, and on the North, East and South by public domain. The Rattler lode, Sur. No. 850, is practically covered by the Pay-Roll-lode.....

#### INSTRUMENT

This survey was made with a W. & L. E. Gurley light mountain transit.

The courses were deflected from a true meridian as determined by direct solar observation.

The distances were measured with a 660 ft. steel tape.

#### REPORT -

The public land corner to which this survey is tied is a bronze capped pipe properly set and marked.

The corners of the Rattler lode, Sur. No. 850 are 4x4 posts upon which the scribed markings are very faint, the survey having been executed during 1873, and no local person knew of its existence, as it has been abondoned for many years. The corners on the Burlock lode Sur.No.3520 are of 4x4 posts properly set and marked, the true point for Cor. No. 4 being N. 72° 53' E. 9.75 ft. The corners on the witness corner therefor.

visted from point one engage

ed Jr Simil espen work be-

abot elos ya

esta di cara anali se in

L LIMI was been raid as therefor

SHOP AND THE THE AND THE TOTAL

de la companya de la

THE ROLL OF THE PARTY OF THE PA

ned account hereal no the

.m. idev unedo -meloco)

the large terms of the same

## FINAL OATHS FOR SURVEYS.

### LIST OF NAMES.

A list of the	names of the individuals e	mployed by Harry E. Jones	
		in running, measuring, and marking the	
boundaries descri	bed in the foregoing field n	notes of the survey of the mining claim of	
		ott.	
		ACK PRINCE lodes	
	respective capacities in which		
		S. J. Byers,	<i>C</i> 2
		E. Ross Housholder,	
			, Flagman.
	FINAL OATH	HS OF ASSISTANTS.	
We,	J. Byers,		
		, do solemnly swear that we assisted	
		ses Mineral Surveyor, in marking the corne	
		, , ===================================	
		lack Prince lodes	
		ving been surveyed by said mineral survey	
lirection; and that	t said survey has been in all	respects, to the best of our knowledge and	belief, faithfully
and correctly execu	ted, and the corner and boun	dary monuments established according to lav	w and the instruc-
ions furnished by t	Office Cadastral he <del>United States Surveyor (</del>	Engineer, at Phoenix, Arizon	ja.
		Byers	, Chainman.
		Elforo Housholder	Chainman
			, Olatiman.
			, Axman.
		y the above-named persons before me this	10th.
	day ofJuly	, 19 36: / /	0
		At Smile	
		Notary Publ	-i-G
		122	6—1043

My Vommission expires april 30 1930.

## FINAL OATH OF U. S. MINERAL SURVEYOR.

I, Harry E. J	Ones, U. S. Mineral Surveyor,
do solemnly swear that, in pursuance of ins	structions received from the Office Cadastral Engineer,
at Phoenixlarizona.	, dated <u>April 21at. 1926</u>
I have, in strict conformity to the laws of t	he United States, the official regulations and instruc-
tions thereunder, and the instructions of sa	id Office Cadastral Engineer, faithfully and correctly
executed the survey of the Mining Claim of	
Thomas B. Scott	, known as the
ray noil and Black	Frince lodes
situate in Wallapai	Mining District
Mohave	County, Arizona , in Section
Township No. 23 N., F	Range No. 18 W. G&SRB&M.
and designated as Survey No. 4009	, as represented
in the foregoing field notes, which accurately	show the boundaries of said mining claim as distinctly
marked by monuments on the ground, and o	lescribed in the attached copy of the location certifi-
cate, which was received by me from the Of	fice Cadastral Engineer with said instructions, and
that all corners of said survey have been est	tablished and perpetuated in strict accordance with
the law, official regulations and instructions t	thereunder; and I do further solemnly swear that the
foregoing are the true and original field notes	s of said survey and my report therein, and that the
labor expended and improvements made upon	n said mining claim by claimant or his
grantors are as therein fully stated, and that	the character, extent, location, and itemized value
thereof are specified therein with particularity	by and full detail, and that no portion of said labor
or improvements so credited to this claim has	been included in the estimate of expenditures upon
any other claim.	upon
	Hauf Jours
	U. S. Mineral Surveyor.
Subscribed and sworn to by the said HE	
U. S. Mineral Surveyor, before me	notary public in and for the County
of Maricopa, State of Ariz	ona this 2nd.
day of August , 1926.	71
	le le
	meg Junes
	Notary Public.

My commission expires August 27th. 1927.

### U. S. SURVEYOR-GENERAL'S FINAL CERTIFICATE ON FIELD NOTES.

# Department of the Interior,

## OFFICE OF U. S. SURVEYOR-GENERAL, PUBLIC SURVEY OFFICE

	P00000	Phoeni	t, Arizona,		
			Mar	ch31	, 1927
I, U. S. Surveyor G	eneral for office ca	DASTRAL_ENGINEER			
do hereby certify that th					
of the mining claim of					
known as the					
situate in					
Mining District,					
in Section2					
designated as Survey No					
this office; that said Fie					
incorporated into a paten					
to natural objects or pern					
And I further certif					
or for eac ments made upon said n	ch of	imant h	4e	been expen	ded or improve-
consist of 2 shafts					
from 4 levels,					
					***************************************
6 5					
and that no portion of sa	id labor or improv	ements has be	een included in t	he estimate	of expenditures
ipon any other claim.					
I further certify that	the plat thereof, fil	led in the U.	S. Land Office at	Phoen1	х,
Arizona	is correct an	d in conformi	ty with the fore	going Field I	Notes.
		John	n D. Adame		
	United Ste	ter Surveyor 6	icneral for Office	CADASTRAL ENG	NEFR.

# CERTIFICATE OF APPROVAL OF FIELD NOTES AND SURVEY OF MINING CLAIM

## DEPARTMENT OF THE INTERIOR PUBLIC SURVEY OFFICE

		At. Phoenix, B	rizona,	
			March 31	, 1927
I, Office Cadastral	Engineer atPho	enix, Arizona,	,	
do hereby certify that	the foregoing and hereto att	ached Field Notes and	d Return of the	Survey of the
Mining Claim of				
	Thomas B. S	cott		,
	AY ROLL and BLACK			
	Wallapai			
Mo	na ve Cou	nty,	Arizona	
in Section2	, Township No	23 North	, Range No	18 West
, d	esignated as Survey No	4009		
executed by	Harry E. Jones			, U. S. Mineral
Surveyor,	July 9 - 10	, 1926	, under my inst	cructions dated
April 21	, 1926	, have been criticall	y examined and	l the necessary
corrections and explana	tions made, and the said Fie	ld Notes and Return,	and the Survey	they describe,
are hereby approved.	The certified copy of the loc	ation certificate filed l	by the applicar	nt for survey is
on file in this office and	d a true copy of said certific	ed copy of said locati	ion certificate is	s included and
nade a part of the trans	cript of the field notes.			

Office Cadastral Engineer, Phoenix, Arizona

COVERNMENT PRINTING OFFICE